

Data sheet

Coupling plug (NW7,2) 4mm hose, Brass

Item number:

KSS 4 NW7



Example illustration

Item description

Materials:

Housing: brass, nickel-plated brass, hardened steel or stainless steel 1.4305, seal: NBR (stainless steel: FKM)

Temperature range:

-20°C to max. +100°C (stainless steel: -15°C to max. +200°C, plastic sleeve max. +80°C)

Operating pressure:

-0,95 to 35 bar

Flow*:**

Standard: 1100 l/min, ball lock: 1850 l/min, ball lock & plastic sleeve: 2100 l/min (each coupling in conjunction with blocking coupling plug **-BA**: 800 l/min)

Note:

Coupling plugs with valve for double-sided shut off **(-BA)** can only be used with the special coupling sockets **(-BA)** provided for them.

Compatible with:**

Rectus (25, 26, 1600, 1625), TEMA (1600), CEJN (320), JWL (520, 530, 560), Legris (25, 26), Parker (PE, PEF), Prevost (E ... 07), Festo (KD4 / KS4 / NPHS), IMI-Norgren (238), Aventics (CP1-NW 7 / 7.8) and many other German brands

Optional:

Body made from 1.4404 **-ES4A**, with valve for double-sided shut-off **-BA**

Properties

Material	Brass
Hose Ø inside [mm]	4
shut-off on both sides	no

Temperature range [°C]	-20 to +200
-------------------------------	-------------

Further information:

Weight	12 g / pcs
GTIN	4050571153731
Customs duty number	84812090
RoHS compliant	Yes