

Fittings aus Messing

Brass fittings

Raccorderia Filettata Generica in Ottone

Technische Daten

Betriebstemperatur	max. +150 °C	
Betriebsdruck	bis 60 bar	
Werkstoffe	Messing vernickelt und blank	CW614N und CW617N
Gewinde	DIN 3852 DIN 3858	
Medium	Luft, Wasser, Öl, Dampf, etc.	

Technical Data

Operating temperature	max. +150 °C	
Operating pressure	Up to 60 bar	
Materials	Brass nickel-plated and polished	CW614N and CW617N
Thread	DIN 3852 DIN 3858	
Medium	Air, water, oil, steam, etc.	

Dati tecnici


Temperatura di esercizio	Max. +150 °C	
Pressione di esercizio	Fino a 60 bar	
Materiali	Ottone (Ms58) nichelato o lucidato	
Filetto	DIN 3852 DIN 3858	
Fluidi utilizzabili	Aria compressa, acqua calda e fredda, olio, vapore, olii e liquidi industriali a richiesta	

RC321

vernickelt, Innensechskant ohne Bund

Male plug conical

Tappo conico a scomparsa con esagono incassato



Code	G	L	O
RC321-1/8	R1/8	8	5
RC321-1/4	R1/4	10	6
RC321-3/8	R3/8	11	8
RC321-1/2	R1/2	13	10
RC321-3/4	R3/4	15,5	14