



SFEX

Schalldämpfer - Edelstahl
Silencer - INOX
Silenziatore in Acciaio



Code	G	H1	H2	L	
SFEX-M5	M5	4	3	8	8
SFEX-1/8	G1/8	6	4	16	13
SFEX-1/4	G1/4	9	4	19	16
SFEX-3/8	G3/8	9	4	21	19
SFEX-1/2	G1/2	10	4	22	24
SFEX-3/4	G3/4	10	4	27	30
SFEX-1	G1	15	4	29	36

Material:	Edelstahl AISI 316L
Material:	Inox AISI 316L
Materiale:	Inox AISI 316L
Filterfeinheit	70µ
Filter mesh:	70µ
Elemento filtrante:	70µ
Betriebsdruck:	max. 10 bar
Working pressure:	max. 10 bar
Pressione di utilizzo:	max. 10 bar
Betriebstemperatur:	-20°C bis +300°C
Working temperature:	-20°C up to +300°C
Temperatura di utilizzo:	da -20°C a +300°C
zyl. Gewinde:	DIN EN ISO 228
cyl. threads:	DIN EN ISO 228
Filettatura	DIN EN ISO 228
metr. Gewinde:	DIN EN ISO 262
metr. threads:	DIN EN ISO 262
Filettatura metrica	DIN EN ISO 262