



STX41

Drosselrückschlagventil mit Ringstück, Typ B, Abluft drosselbar

Unidirectional flow regulator type B for cylinders (stainless steel)

Regolatore di flusso unidirezionale per cilindro - Inox



| Code | ØD | G | H | L1 max | L2 |  |
|-------------|----|------|-----|--------|------|---|
| STX41-4-M5 | 4 | M5 | 3,7 | 24 | 19,5 | 8 |
| STX41-4-1/8 | 4 | G1/8 | 7 | 32 | 21,0 | 14 |
| STX41-6-M5 | 6 | M5 | 3,7 | 24 | 21,5 | 8 |
| STX41-6-1/8 | 6 | G1/8 | 7 | 32 | 22,5 | 14 |
| STX41-6-1/4 | 6 | G1/4 | 8 | 40 | 24,5 | 17 |
| STX41-8-1/8 | 8 | G1/8 | 7 | 32 | 24,0 | 14 |
| STX41-8-1/4 | 8 | G1/4 | 8 | 40 | 26,0 | 17 |

Körper: AISI 316L

Body: AISI 316L

Corpo: AISI 316L

O-Ring: FKM

O-ring: FKM

O-Ring: FKM

Dichtungen: FKM

Seals: FKM

Rondella di tenuta sul filetto: FKM

zyl. Gewinde: DIN EN ISO 228

cyl. Threads: DIN EN ISO 228

Filettatura: gas cilindrica ISO 228

Betriebstemperatur: -20 °C bis +150 °C

Working temperature: -20 °C up to +150 °C

Temperatura di utilizzo: da -20 °C a +150 °C

Betriebsdruck: -0,98 bis 16 bar

Working pressure: -0,98 up to 16 bar

Pressione di utilizzo: da -0,98 a 16 bar

Für geölte und ungeölte Druckluft.

For lubricated and non-lubricated compressed air.

Per aria compressa sia lubrificata che non.