

# Data sheet

---

## Ersatzmembrane für ZS 38, ZS 12, ZS 34 aus FKM

**Item number:**

ZS 381234 MEM V

### Item description

**Materials:**

Bodies: brass, internal parts: brass / stainless steel, seal: NBR

**Temperature range:**

-10°C to max. +80°C, ambience: max. +65°C

**Operating pressure:**

DC: 0 - 6 bar, AC: 0 - 10 bar

**Power consumption:**

Direct current (DC): 20 W, G 1-1/4" - G 2": 45 W, alternating current (AC): 24 VA, G 1-1/4" - G2": 36 VA (draw 60 / 90 VA)

**Media:**

Compressed air, neutral gases, water, neutral low-viscosity media, other media on request

**Installation position:**

With upright magnets

**Voltages:**

Standard: 24 V=, 230 V AC, upon request: other voltages

**Protection class:**

IP 65 (plug size 3)

**Optional:**

FKM seal (-10°C to max. +130°C) **-V**, EPDM seal for air and warm water (-10°C to max. +120°C) **-EP**

**Information:**

These valves are generally delivered with coils and plugs!

### Further information:

<b>Weight</b>	18 g / Pcs
---------------	------------

<b>GTIN</b>	4050571817053
<b>Customs duty number</b>	40169300
<b>RoHS compliant</b>	Yes
<b>Manufacturer</b>	EMC