

Data sheet

Pressure gauge horizontal (KU/Ms), 50mm, 0 to 6 bar, G 1/4"

Item number:

MW 650



Example illustration

Item description

Materials:

Housing: black plastic, measuring system and connection: Cu alloy, window: transparent plastic

Connection thread:

G 1/4" * (Ø 40: G 1/8"), back-mounted, centred

Class:

2,5

Temperature range:

-20°C to +60°C

Dial:

1. Scale outside (black), display in bar, 2. scale inside (red), display in PSI

Protection class:

IP 42

Note:

WIKA Type 111.12

Optional:

Housing made of sheet steel, class 1.6 -**ST**, ISO factory calibration (following DIN EN 837-1, determination of measurement deviation and hysteresis), DAkKS-DKD calibration (in accordance with DKD-R 6-1, traceable and accredited in accordance with DIN EN ISO/IEC 17025, decision rule 4)

Properties

| | |
|----------------------------|----------|
| Diameter [mm] | 50 |
| Connection thread | G 1/4" * |
| Display range [bar] | 0 - 6 |

| | |
|-----------------------------|----------|
| Scale division [bar] | 0,2 |
| Version | Standard |

Further information:

| | |
|----------------------------|---------------|
| Weight | 75 g / pcs |
| GTIN | 4050571514365 |
| Customs duty number | 90262040 |
| RoHS compliant | Yes |
| Manufacturer | Wika |